

MOBILE TANKS TYPE IC-BOX UP TO 3m³



MOBILE TANKS TYPE IC-BOX UP TO 3m³

CONSTRUCTION AND EQUIPMENT OF THE TANK:

- > Carbon steel double wall tank, material according to EN-10025-2
- > Mobile tank designed for easy transport
- > Lifting handles, handles for trucks, shipping brackets
- > Internal paint attested to aviation fuel
- > External paint polyurethane paint white or gray
- > Tank cap mounted on cylinders
- > Overfill protection system
- > Drain and purge system
- > Special fuel circuit protection against water and dirt
- > Outlet pipe with a breathing vent valve and a flame arrester
- > Transfer system of tanker with VRS, flame arrester
- > Inspection hole (stainless steel INOX)
- > Tank fittings resistant to aggressive agents which are components of aviation fuel
- > Tank leak monitoring sensor with alarm panel and probe
- > Float level gauge in the tank
- > Could be mounted on a trailer

IBC tank capacity	Fuel tank dimensions	External tank dimension	Weight
V[I]	AxBxH mm]	AxBxH [mm]	[kg]
600	870x1130x620	1330x1170x865	410
800	870x1130x820	1330x1170x1030	450
995	1065x1130x830	1535x1170x1030	490
1150	1230x1130x830	1710x1170x1030	575
1600	1750x1130x830	2260x1170x1030	720
2000	1660x1130x1070	2160x1170x1280	810
3000	2650x1070x1070	3060x1170x1280	1150

3000 2650x1070x1070 3060x1170x1280


DISTRIBUTION SET:

- > Pump EX with flow rate up to 144 I/min
- > Mechanic and electronic meters
- > Hose reel length 15m, diameter 1" (width 28 cm, length 55cm, height 58 cm)
- > Fuel hose DN-25 10m; both sides provided with a metal tip
- Hand pump for pumping the remaining fuel from the tank ePM-GIM
- > Aviation fuel filter EN-VFC-1/254-10, filter up to 1um, flow rate 56 l/min or higher
- > Grounding reel (manual) 15m, type Mle-15
- > Automatic grounding reel 15m, type AMIe-15
- > Grounding clamp

eN-TANK Sp. J. ul. Geodetów 1 Street 64-100 Leszno POLAND









+48 607 747 011 +48 603 747 917 en-tank@en-tank.pl