Fuelling products

Couplings

2 1/2 and 3-inch stainless steel self sealing industrial couplings

Specification

TANK UNIT THREADED VERSION

3 - 2.5-IN BSP CCMY 8251 4 - 3-IN BSP CCMY 8252

Material 316 Stainless Steel

Weight 3 kg
Max. Working Pressure 300 psi
Max. Coupling Pressure 60 psi

5 - TANK UNIT CCMY 8250

2.5-IN FLANGED VERSION

Material 316 Stainless Steel

Weight 4 kg
Max. Working Pressure 300 psi
Max. Coupling Pressure 60 psi

Flanged tank units can be drilled to customers requirements on request

6 - DUST COVER CCMY 1271

Material Stainless Steel


Seals

Hose and Tank units are available with a choice of seals:


Seal Material Pt. No. Suffix

Viton V
Nitrile N
Chemraz C
E.P. E


3 CCMY 8251



4 CCMY 8252



5 CCMY 8250



Fuelling products


Couplings

2 1/2 and 3-inch stainless steel self sealing industrial couplings

Key Dimensions

PRESSURE DROP

PRODUCT: Distillate Specific gravity at 15 deg / 15 deg C = 0.80 Viscosity at 15 deg C = 2.4 centistokes



Contact

HP Aviation Group

Address: 1/9 Newry Drive, New Gisborne, 3438, Australia

Telephone: +61 35428 4846 +61 400 234 997

Email:

sales@hpaviationhoses.com.au


Website:


www.hpaviationhoses.com.au

SELECTIVITY

To avoid product contamination caused by connecting a hose unit to the wrong tank unit, selective versions of the hose and tank units are available.

| Selective Position Letter | Α | В | С | D | Е | F | G |
|---------------------------|-----|-----|-----|-----|-----|-----|-----|
| Pin & Slot Position | 1&2 | 1&3 | 1&4 | 1&5 | 1&6 | 1&7 | 2&3 |
| Selective Position Letter | Н | J | K | L | М | Ν | Р |
| Pin & Slot Position | 2&4 | 2&5 | 2&6 | 2&7 | 3&4 | 3&5 | 3&6 |
| Selective Position Letter | Q | R | S | Т | U | ٧ | W |
| Pin & Slot Position | 3&7 | 4&5 | 4&6 | 4&7 | 5&6 | 5&7 | 6&7 |





Meggitt Control Systems

